

Data sheet for SINUMERIK Operator panel front

MLFB-Ordering data 6FC5203-0AF05-1AB1



Figure similar

Client order no. : Item no. :
Order no. : Consignment no. :
Offer no. : Project :
Remarks :

Remarks :			
Screen		Ambient conditions	
Screen diagonal	15 in TFT color XGA		
Screen resolution	1024 x 768 Pixel	Climate class according to EN60721- 3-3	Condensation and icing excluded Low air temperature 0 °C (32 °F).
F	Rated data		
Input voltage	DC 24 V	Ambient temperature	
		Operation on the front	0 45 %
		Operation at the rear	0 55 %
Power consumption		Storage	-20 55 °C
Maximum	48 W	Transport	-20 55 °C
Standard	22 W	Relative humidity	
Mechanical data		Operation	5 95 %
Net weight	7.60 kg	Storage	5 95 %
Width	483.0 mm	Transport	5 95 %
Height	355.0 mm	Approvals	
Depth	53.0 mm	Approvals	
	Without USB protective cover on the front	Certificate of suitability	CE, cULus
Installation depth	42.0 mm		
	Clearance + 10 mm (0.39 in)		
Degree of protection			
Front side	IP65		
Rear side	IP00		
Mounting surface			
Cutout width	450.0 mm		

335.0 mm

Cutout height