

SIMATIC S7-300, CPU 312C COMPACT CPU WITH MPI, 10 DI/6 DO, 2 FAST COUNTERS (10 KHZ), INTEGRATED 24V DC POWER SUPPLY, 16 KBYTE WORKING MEMORY, FRONT CONNECTOR (1 X 40PIN) AND MICRO MEMORY CARD REQUIRED

General information	
Hardware product version	01
Firmware version	V2.0
Engineering with	
• Programming package	STEP 7 V5.2 SP1 or higher
Supply voltage	
Rated value (DC)	
• 24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	500 mA
Current consumption (in no-load operation), typ.	60 mA
Inrush current, typ.	3 A
Power loss	
Power loss, typ.	6 W
Memory	
Work memory	
• integrated	16 kbyte; For program and data
• expandable	No
Load memory	
• Plug-in (MMC)	Yes
• Plug-in (MMC), max.	4 Mbyte
• Data management on MMC (after last programming), min.	10 y
Backup	
• present	Yes; Guaranteed by MMC (maintenance-free)
• without battery	Yes; Program and data

CPU processing times	
for bit operations, typ.	0.2 µs
for bit operations, max.	0.4 µs
for word operations, typ.	0.4 µs
for fixed point arithmetic, typ.	5 µs
for floating point arithmetic, typ.	6 µs
CPU-blocks	
Number of blocks (total)	1 024; (DBs, FCs, FBs OBs, SDBs); the maximum number of loadable blocks can be reduced by the MMC being used.
DB	
• Number, max.	511; Number range: 1 to 511
• Size, max.	16 kbyte
FB	
• Number, max.	512; Number range: 0 to 2047
• Size, max.	16 kbyte
FC	
• Number, max.	512; Number range: 0 to 2047
• Size, max.	16 kbyte
OB	
• Number, max.	see instruction list
• Size, max.	16 kbyte
• Number of free cycle OBs	1; OB 1
• Number of time alarm OBs	1; OB 10
• Number of delay alarm OBs	1; OB 20
• Number of cyclic interrupt OBs	1; OB 35
• Number of process alarm OBs	1; OB 40
• Number of startup OBs	1; OB 100
• Number of asynchronous error OBs	1; OB 80
• Number of synchronous error OBs	2; OB 121, 122
Nesting depth	
• per priority class	8
• additional within an error OB	4
Counters, timers and their retentivity	
S7 counter	
• Number	128
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	128
Counting range	
— lower limit	0

— upper limit	999
IEC counter	
• Number	Unlimited (limited only by RAM capacity)
S7 times	
• Number	128
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	128
— preset	No retentivity
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
Data areas and their retentivity	
retentive data area in total	all
Flag	
• Number, max.	128 byte
• Retentivity available	Yes; MB 0 to MB 127
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte
Data blocks	
• Number, max.	511; from DB1 to DB511
• Size, max.	16 kbyte
• Retentivity adjustable	No
• Retentivity preset	Yes
Local data	
• per priority class, max.	256 byte
Address area	
I/O address area	
• Inputs	1 kbyte
• Outputs	1 kbyte
Process image	
• Inputs	128 byte
• Outputs	128 byte
Default addresses of the integrated channels	
— Digital inputs	124.0 to 125.1
— Digital outputs	124.0 to 124.5

Digital channels	
• Inputs	256
— of which central	256
• Outputs	256
— of which central	256
Analog channels	
• Inputs	64
• Outputs	32
Hardware configuration	
Number of expansion units, max.	0
Number of DP masters	
• integrated	none
• via CP	4
Number of operable FMs and CPs (recommended)	
• FM	8
• CP, PtP	8
• CP, LAN	4
Rack	
• Racks, max.	1
• Modules per rack, max.	8
Time of day	
Clock	
• Software clock	Yes
• retentive and synchronizable	No
Operating hours counter	
• Number	1
• Number/Number range	0
• Range of values	0 to 2 ³¹ hours (when using SFC 101)
• Granularity	1 hour
• retentive	Yes; Must be restarted at each restart
Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• in AS, master	Yes
Digital inputs	
Number of digital inputs	10
integrated channels (DI)	10
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-3 to +5V

• for signal "1"	+15 to +30V
Input current	
• for signal "1", typ.	8 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.1 / 0.3 / 3 / 15 ms
for counter/technological functions	
— at "0" to "1", max.	50 µs
Cable length	
• shielded, max.	1 000 m; 100 m for technological functions
• unshielded, max.	600 m
Digital outputs	
Number of digital outputs	6
integrated channels (DO)	6
Short-circuit protection	Yes; Clocked electronically
Limitation of inductive shutdown voltage to	L+ (-48 V)
Output voltage	
• for signal "1", min.	L+ (-0.8 V)
Output current	
• for signal "1" permissible range, max.	500 mA
• for signal "1" permissible range for 0 to 60 °C, max.	500 mA
• for signal "1" minimum load current	5 mA
• for signal "0" residual current, max.	0.5 mA
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
Total current of the outputs (per group)	
all mounting positions	
— up to 40 °C, max.	3 A
— up to 60 °C, max.	1.5 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Analog inputs	
integrated channels (AI)	none
Analog outputs	
integrated channels (AO)	none
Encoder	
Connectable encoders	
• 2-wire sensor	Yes

— permissible quiescent current (2-wire sensor), max.

1.5 mA

Interfaces

MPI

- Cable length, max. 50 m; without repeater

1. Interface

Interface type Integrated RS 485 interface

Physics RS 485

Isolated No

Power supply to interface (15 to 30 V DC), max. 200 mA

Functionality

- MPI Yes
- PROFIBUS DP master No
- PROFIBUS DP slave No
- Point-to-point connection No

MPI

- Number of connections 6
- Transmission rate, max. 187.5 kbit/s

Services

- PG/OP communication Yes
- Routing No
- Global data communication Yes
- S7 basic communication Yes
- S7 communication Yes
- S7 communication, as client No
- S7 communication, as server Yes

Communication functions

PG/OP communication Yes

Global data communication

- supported Yes
- Number of GD loops, max. 4
- Number of GD packets, max. 4
- Number of GD packets, transmitter, max. 4
- Number of GD packets, receiver, max. 4
- Size of GD packets, max. 22 byte
- Size of GD packet (of which consistent), max. 22 byte

S7 basic communication

- supported Yes
- User data per job, max. 76 byte
- User data per job (of which consistent), max. 76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server)

S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes; Via CP and loadable FB
• User data per job, max.	180 byte
• User data per job (of which consistent), max.	64 byte
S5 compatible communication	
• supported	Yes; via CP and loadable FC
Number of connections	
• overall	6
• usable for PG communication	5
— reserved for PG communication	1
— adjustable for PG communication, min.	1
— adjustable for PG communication, max.	5
• usable for OP communication	5
— reserved for OP communication	1
— adjustable for OP communication, min.	1
— adjustable for OP communication, max.	5
• usable for S7 basic communication	2
— reserved for S7 basic communication	2
— adjustable for S7 basic communication, min.	0
— adjustable for S7 basic communication, max.	2
• usable for routing	No
S7 message functions	
Number of login stations for message functions, max.	6; Depending on the configured connections for PG/OP and S7 basic communication
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	20
Test commissioning functions	
Status block	Yes
Single step	Yes
Number of breakpoints	2
Status/control	
• Status/control variable	Yes
• Variables	Inputs, outputs, memory bits, DB, times, counters
• Number of variables, max.	30
— of which status variables, max.	30
— of which control variables, max.	14
Forcing	

- Forcing
- Forcing, variables
- Number of variables, max.

Yes
Inputs, outputs
10

Integrated Functions

Number of counters	2; 2 channels (see "Technological Functions" manual)
Counting frequency (counter) max.	10 kHz
Frequency measurement	Yes
Number of frequency meters	2; 2 channels up to max. 10 kHz (see "Technological Functions" manual)
controlled positioning	No
integrated function blocks (closed-loop control)	No
PID controller	No
Number of pulse outputs	2; 2 channels pulse width modulation up to 2.5 kHz (see Manual "Technological Functions")
Limit frequency (pulse)	2.5 kHz

Potential separation

Potential separation digital inputs	
• Potential separation digital inputs	Yes
• between the channels, in groups of	10
• between the channels and backplane bus	Yes
Potential separation digital outputs	
• Potential separation digital outputs	Yes
• between the channels, in groups of	6
• between the channels and backplane bus	Yes

Configuration

Configuration software	
• STEP 7	Yes; V5.1 SP2
Programming	
• Command set	see instruction list
• Nesting levels	8
• System functions (SFC)	see instruction list
• System function blocks (SFB)	see instruction list
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— GRAPH	Yes
— HiGraph®	Yes
Know-how protection	
• User program protection/password protection	Yes

Dimensions	
Width	80 mm
Height	125 mm
Depth	130 mm
Weights	
Weight, approx.	409 g
last modified:	08/12/2017