

JUNCTION BOX PLUS FOR MOBILE PANEL 170

| | |
|---|--|
| Control elements | |
| Expansions for operator control of the process | |
| • Hot swapping | without emergency stop circuit interruption |
| • Monitoring the STOP button | Yes |
| • Location identifier | Yes |
| Supply voltage | |
| Type of supply voltage | 24 V DC |
| Input current | |
| Current consumption (rated value) | 0.5 A |
| Power | |
| Active power input, typ. | 12 W |
| Interfaces | |
| Interfaces/bus type | 1 x RS232, 1 x RS422, 1 x RS485 (max. 12 Mbit/s) |
| Number of RS 485 interfaces | 1 |
| Degree and class of protection | |
| Degree of protection acc. to EN 60529 | IP65 |
| Standards, approvals, certificates | |
| Certifications | CE, cULus |
| cULus | Yes |
| RCM (formerly C-TICK) | No |
| Ambient conditions | |
| Ambient temperature during storage/transportation | |
| • min. | -20 °C |
| • max. | 70 °C |
| Relative humidity | |
| • Operation, max. | 85 % |
| Weights | |
| Weight (without packaging) | 0.4 kg |
| Other | |
| free hotline | Yes |
| Warranty period | 1 y |
| last modified: | 08/12/2017 |