

SPARE PART LOGO!12/24RCE,LOGIC MOD.,DISPL. PU/I/O:
12/24V DC/RELAY, 8 DI (4AI)/4 DO; MEM 400 BLOCKS
EXPANDABLE, ETHERNET



Display	
with display	Yes
Installation type/mounting	
Mounting	on 35mm DIN rail, 6 spacing units wide
Supply voltage	
Rated value (DC)	
• 12 V DC	Yes
• 24 V DC	Yes
permissible range, lower limit (DC)	10.8 V
permissible range, upper limit (DC)	28.8 V
Time of day	
Time switching clocks	
• Number	333
• Power reserve	480 h
Digital inputs	
Number of digital inputs	8; Of which 4 can be used in analog mode (0 to 10 V)
Digital outputs	

Number of digital outputs	4
Short-circuit protection	No; external fusing necessary
Relay outputs	
Switching capacity of contacts	
— with inductive load, max.	3 A
— with resistive load, max.	10 A

EMC

Emission of radio interference acc. to EN 55 011	
• Limit class B, for use in residential areas	Yes; Radio interference suppression according to EN55011, Limit Value Class B

Degree and class of protection

Degree of protection acc. to EN 60529	
• IP20	Yes

Standards, approvals, certificates

CE mark	Yes
CSA approval	Yes
UL approval	Yes
FM approval	Yes
developed in accordance with IEC 61131	Yes
according to VDE 0631	Yes
Marine approval	Yes

Ambient conditions

Ambient temperature during operation	
• min.	0 °C
• max.	55 °C

Dimensions

Width	107 mm
Height	90 mm
Depth	55 mm
last modified:	08/12/2017