

Data sheet for SINUMERIK Operator panel front

MLFB-Ordering data

6FC5203-0AF08-0AB2

Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Screen		Ambient conditions	
Screen diagonal	15 in TFT color XGA	Climate class according to EN60721-3-3 Condensation and icing excluded. Low air temperature 0 °C (32 °F).	
Screen resolution	1024 x 768 Pixel		
Rated data		Ambient temperature	
Input voltage	DC 5 V		
	Via PCU or TCU	Operation on the front	0 ... 45 %
		Operation at the rear	0 ... 55 %
Power consumption		Storage	-20 ... 55 °C
		Transport	-20 ... 55 °C
Maximum	25 W	Relative humidity	
Standard	15 W		
Mechanical data		Operation	5 ... 95 %
Net weight	8.40 kg	Storage	5 ... 95 %
Width	483.0 mm	Transport	5 ... 95 %
Height	355.0 mm	Approvals	
Depth	53.0 mm		
	Without USB protective cover on the front	Certificate of suitability	CE, cULus
Installation depth			
with PCU 50	127.0 mm		
	Clearance + 10 mm (0.39 in)		
Degree of protection			
Front side	IP65		
Rear side	IP00		
Mounting surface			
Cutout width	450.0 mm		
Cutout height	335.0 mm		