



⚠ Restricted Sales for Services

## Main

Range of product	Modicon Premium Automation platform
Product or component type	Non-extendable rack
Product specific application	For single rack configuration

## Complementary

Number of slots	12
Product compatibility	I/O module Specific application module TSXPSY power supply TSXP57 processor
Fixing mode	By 4 M6 screws (panel) By clips (35 mm symmetrical DIN rail)
Marking	CE
Net weight	2.31 kg

## Environment

Standards	89/336/EEC UL 508 CSA C22.2 No 213 Class I Division 2 Group C IEC 61131-2 CSA C22.2 No 142 73/23/EEC CSA C22.2 No 213 Class I Division 2 Group B 92/31/EEC CSA C22.2 No 213 Class I Division 2 Group D CSA C22.2 No 213 Class I Division 2 Group A 93/68/EEC
Product certifications	DNV GL RINA RMRS LR ABS BV
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-25...70 °C
Relative humidity	10...95 % without condensation for operation 5...95 % without condensation for storage

Operating altitude	0...2000 m
Protective treatment	Conformal coating Humiseal 1A33 TC
IP degree of protection	IP20
Pollution degree	2

### Contractual warranty

Warranty	18 months
----------	-----------

### TSXRKY12C is replaced by:



#### Harsh environment BMXXBP1200H

ruggedized rack M340 -12 slots - panel or plate mounting

Qty 1

Reason for Substitution: End of life | Substitution date: 31 December 2017