

CONNECTIVITY BOX PN BASIC FOR MOBILE PANELS
(PROFINET)



Figure similar

General information	
Product type designation	PN connection box for Mobile Panel 177/277 (PROFINET) Basic
Control elements	
Expansions for operator control of the process	
• Hot swapping	with emergency stop circuit interruption
• Monitoring the STOP button	No
• Location identifier	Yes
Supply voltage	
Type of supply voltage	24 V DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	0.4 A
Power	
Active power input, typ.	10 W

Interfaces	
Interfaces/bus type	Ethernet
Industrial Ethernet	
• Industrial Ethernet interface	2 x Fast Ethernet
• Industrial Ethernet status LED	6
Degree and class of protection	
Degree of protection acc. to EN 60529	IP65
Standards, approvals, certificates	
Certifications	CE, cULus, C-TICK
CE mark	Yes
CSA approval	No
UL approval	No
cULus	Yes
RCM (formerly C-TICK)	Yes
EAC (formerly Gost-R)	No
Marine approval	No
Use in hazardous areas	
• ATEX Zone 2	No
• ATEX Zone 22	No
• FM Class I Division 2	No
Ambient conditions	
Ambient temperature during operation	
• Operation (vertical installation)	0 to +50 °C
— For vertical installation, min.	0 °C
— For vertical installation, max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	70 °C
Relative humidity	
• Operation, max.	85 %
Functionality under WinCC (TIA Portal)	
Applications/options	
• Connection point identification	Yes
Dimensions	
Width	230 mm
Height	120 mm
Depth	80 mm
Weights	
Weight (without packaging)	0.45 kg

Other	
free hotline	Yes
Warranty period	1 y
Usable in the following products	
• Product 1	6AV6645-0BA01-0AX0
• Product 2	6AV6645-0BB01-0AX0
• Product 3	6AV6645-0BC01-0AX0
• Product 4	6AV6645-0BE02-0AX0
• Product 5	6AV6645-0C*
last modified:	08/12/2017