

Data sheet for SINUMERIK Operator panel front

MLFB-Ordering data

6FC5203-0AF04-0AA0



Figure similar

Client order no. : Item no. :
Order no. : Consignment no. :
Offer no. : Project :
Remarks :

Screen		Ambient conditions	
Screen diagonal	10 in TFT color VGA		
Screen resolution	640 x 480 Pixel	Climate class according to EN60721-3-3	Condensation and icing excluded Low air temperature 0 °C (32 °F).
F	Rated data		
Input voltage	DC 5 V	Ambient temperature	
	Via PCU or TCU	Operation on the front	0 45 %
		Operation at the rear	0 55 %
ower consumption		Storage	-20 55 °C
Maximum	16 W	Transport	-20 55 °C
Standard	10 W	Relative humidity	
Mechanical data		Operation	5 95 %
Net weight	5.50 kg	Storage	5 95 %
Width	310.0 mm	Transport	5 95 %
Height	330.0 mm		
Depth	45.0 mm	Approvals	
	Without USB protective cover on the front	Certificate of suitability	CE, cULus
nInstallation depth			
with PCU 50	120.0 mm		
	Clearance + 10 mm (0.39 in)		
Degree of protection			
Front side	IP54		
Rear side	IP00		
Mounting surface			
Cutout width	285.0 mm		

304.0 mm

Cutout height