

MLFB-Ordering data

6FC5203-0AF05-0AB0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. : Consignment no. : Project :

Screen		Ambient conditions	
Screen diagonal	15 in TFT color XGA		
Screen resolution	1024 x 768 Pixel	Climate class according to EN60721- 3-3	Condensation and icing excluded. Low air temperature 0 °C (32 °F).
Rated data]	
Input voltage	DC 5 V	Ambient temperature	
	Via PCU or TCU	Operation on the front	0 45 %
Power consumption		Operation at the rear	0 55 %
Maximum	25 W	Storage	-20 55 °C
		Transport	-20 55 °C
Standard	15 W	Relative humidity	
Mechanical data		Operation	5 95 %
Net weight	8.40 kg	Storage	5 95 %
Width	483.0 mm	Transport	5 95 %
Height	355.0 mm	Approvala	
Depth	53.0 mm	Approvals	
	Without USB protective cover on the front	Certificate of suitability	CE, cULus
InInstallation depth			
with PCU 50	127.0 mm		
	Clearance + 10 mm (0.39 in)		
Degree of protection			
Front side	IP65		
Rear side	IP00		
Mounting surface			
Cutout width	450.0 mm		
Cutout height	335.0 mm		