



ⓘ Restricted Sales for Services

Main

Range of product	Modicon Premium Automation platform
Product or component type	Ethernet TCP/IP module
Physical interface	AUI - 100BASE-5 1 AUI cable RJ45 - 10BASE-T 1 twisted pair
Transmission rate	10 Mbit/s
Communication service	Modbus TCP messaging Optional TCP open SNMP agent Uni-TE messaging Common words, Ethway/X-Way Application to application, Ethway/X-Way
Supply	Via the power supply of the rack
Local signalling	1 LEDcollision detection (COL): 1 LEDEthernet network status (RUN): 1 LEDEthernet port fault (ERR): 1 LEDtransmission/reception activity (TX/TR):

Complementary

Communication port protocol	Modbus TCP Uni-Telway Ethway/X-Way
Maximum number of connections	64
Web server	Transparent ready class C10
Web feature	Data Editor (via PC terminal) Rack viewer FactoryCast configurable
Memory description	User web page size 1.4 MB
Marking	CE
Product compatibility	PL7 Pro
Current consumption	1200 mA 5 V DC with remote power supply (AUI) 800 mA 5 V DC without remote power supply (RJ45)
Module format	Standard
Net weight	0.37 kg

Environment

Standards	FM Class 1 Division 2 group C
-----------	-------------------------------

FM Class 1 Division 2 group B
FM Class 1 Division 2 group D
EN 61131-2
FM Class 1 Division 2 group A

Product certifications	UL 508 CSA 1010-1
IP degree of protection	IP20
Protective treatment	Conformal coating Humiseal 1A33
Ambient air temperature for operation	0...60 °C
Relative humidity	10...95 % at 60 °C without condensation

Contractual warranty

Warranty	18 months
----------	-----------

TSXETY110WSC is replaced by:



Standard environment BMXNOE0100

Ethernet module M340 - flash memory card - 1 x RJ45 10/100

Qty 1

Reason for Substitution: End of life | Substitution date: 31 December 2017