

SIMATIC S7-400, CPU 412-1 Central processing unit with: work memory 144 KB (72 KB code, 72 KB data), interface MPI/DP 12 Mbit/s,



General information	
Firmware version	V4.0
Engineering with	
• Programming package	STEP 7 V5.2 SP1 HF3 or higher with HW update
CiR – Configuration in RUN	
CiR synchronization time, basic load	100 ms
CiR synchronization time, time per I/O byte	200 μs
Supply voltage	
Rated value (DC)	Yes
• 24 V DC	
Input current	
from backplane bus 5 V DC, typ.	0.6 A
from backplane bus 5 V DC, max.	0.7 A
from backplane bus 24 V DC, max.	The CPU uses no current at 24 V, it provides this voltage only at the MPI-/DP interface.
Power loss	
Power loss, typ.	3 W

Memory	
Work memory	
• integrated (for program)	72 kbyte
• integrated (for data)	72 kbyte
• expandable	No
Load memory	
• expandable FEPR0M	Yes; with Memory Card (FLASH)
• expandable FEPR0M, max.	64 Mbyte
• integrated RAM, max.	256 kbyte
• expandable RAM	Yes; with Memory Card (RAM)
• expandable RAM, max.	16 Mbyte
Backup	
• present	Yes
• with battery	Yes; all data
• without battery	No
Battery	
Backup battery	
• Backup current, typ.	350 μ A
• Backup current, max.	890 μ A
• Backup time, max.	226 d
• Feeding of external backup voltage to CPU	5 V DC to 15 V DC
CPU processing times	
for bit operations, typ.	0.1 μ s
for word operations, typ.	0.1 μ s
for fixed point arithmetic, typ.	0.1 μ s
for floating point arithmetic, typ.	0.3 μ s
CPU-blocks	
DB	
• Number, max.	512; DB 0 reserved
• Size, max.	64 kbyte
FB	
• Number, max.	256
• Size, max.	64 kbyte
FC	
• Number, max.	256
• Size, max.	64 kbyte
OB	
• Number, max.	see instruction list
• Size, max.	64 kbyte
Nesting depth	
• per priority class	24

- additional within an error OB

1

Counters, timers and their retentivity

S7 counter

- Number 2 048
- Retentivity
 - adjustable Yes
 - lower limit 0
 - upper limit 2 047
 - preset Z 0 to Z 7

Counting range

- lower limit 0
- upper limit 999

S7 times

- Number 2 048
- Retentivity
 - adjustable Yes
 - lower limit 0
 - upper limit 2 047
 - preset No times retentive

Time range

- lower limit 10 ms
- upper limit 9 990 s

IEC timer

- present Yes
- Type SFB

Data areas and their retentivity

retentive data area in total Total working and load memory (with backup battery)

Flag

- Number, max. 4 kbyte
- Retentivity available Yes; From MB 0 to MB 4095
- Retentivity preset MB 0 to MB 15
- Number of clock memories 8; 1 memory byte

Local data

- adjustable, max. 8 byte
- preset 4 byte

Address area

I/O address area

- Inputs 4 kbyte
- Outputs 4 kbyte

of which distributed

— MPI/DP interface, inputs	2 kbyte
— MPI/DP interface, outputs	2 kbyte
Process image	
• Inputs, adjustable	4 kbyte
• Outputs, adjustable	4 kbyte
• Inputs, default	128 byte
• Outputs, default	128 byte
• consistent data, max.	244 byte
• Access to consistent data in process image	Yes
Subprocess images	
• Number of subprocess images, max.	15
Digital channels	
• Inputs	32 768
— of which central	32 768
• Outputs	32 768
— of which central	32 768
Analog channels	
• Inputs	2 048
— of which central	2 048
• Outputs	2 048
— of which central	2 048
Hardware configuration	
Number of expansion units, max.	21; of which 6 ER with K-bus
connectable OPs	15 without message processing, 8 with message processing
Multicomputing	Yes; 4 CPUs max. (with UR1 or UR2)
Interface modules	
• Number of connectable IMs (total), max.	6
• Number of connectable IM 460s, max.	6
• Number of connectable IM 463s, max.	4; IM 463-2
Number of DP masters	
• integrated	1
• via CP	10; CP 443-5 Extended
• via IM 467	4
• Mixed mode IM + CP permitted	No; IM 467 cannot be used jointly with CP 443-5 Ext.
• via interface module	0
• Number of pluggable S5 modules (via adapter capsule in central device), max.	6
Number of operable FMs and CPs (recommended)	
• FM	Limited by number of slots and number of connections
• CP, PtP	CP 440: Limited by number of slots; CP 441: limited by number of connections
• CP, LAN	Limited by number of slots and number of connections

• PROFIBUS and Ethernet CPs	14; incl. CP 443-5 Ext. and IM 467
Slots	
• required slots	1
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
• Resolution	1 ms
• Deviation per day (buffered), max.	1.7 s; Power off
• Deviation per day (unbuffered), max.	8.6 s; Power on
Operating hours counter	
• Number	8
• Number/Number range	0 to 7
• Range of values	0 to 32767 hours
• retentive	Yes
Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• to DP, master	Yes
• to DP, slave	Yes
• in AS, master	Yes
• in AS, slave	Yes
1. Interface	
Interface type	Integrated
Physics	RS 485 / PROFIBUS
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	150 mA
Number of connection resources	MPI: 16, DP: 16
Functionality	
• MPI	Yes
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
MPI	
• Number of connections	16
• Transmission rate, max.	12 Mbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes

— S7 communication	Yes
DP master	
• Number of connections, max.	16
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	32
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	Yes
— S7 communication	Yes
— Equidistance	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
Address area	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
DP slave	
• Number of connections	16
• GSD file	http://www.ad.siemens.de/csi_e/gsd
• Transmission rate, max.	12 Mbit/s
• Address area, max.	32
• User data per address area, max.	32 byte
— of which consistent, max.	32 byte
Services	
— PG/OP communication	Yes
— Routing	Yes
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	Yes
Equidistance	Yes

User data per isochronous slave, max.	244 byte
shortest clock pulse	1 ms
max. cycle	32 ms

Communication functions

PG/OP communication	Yes
• Number of connectable OPs without message processing	15
• Number of connectable OPs with message processing	8
Global data communication	
• supported	Yes
• Number of GD loops, max.	8
• Number of GD packets, transmitter, max.	8
• Number of GD packets, receiver, max.	16
• Size of GD packets, max.	64 byte
• Size of GD packet (of which consistent), max.	1 variable
S7 basic communication	
• supported	Yes; in MPI mode via: SFC X_SEND, X_RCV, X_GET and X_PUT; in DP master mode via: SFC I_GET and I_PUT
• User data per job, max.	76 byte
• User data per job (of which consistent), max.	1 variable
S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes
• User data per job, max.	64 kbyte
• User data per job (of which consistent), max.	462 byte; 1 variable
S5 compatible communication	
• supported	Yes; Via FC AG_SEND and AG_RECV, max. via 10 CP 443-1 or 443-5
• User data per job, max.	8 kbyte
• User data per job (of which consistent), max.	240 byte
Standard communication (FMS)	
• supported	Yes; Via CP and loadable FB
Number of connections	
• overall	16
• usable for PG communication	
— reserved for PG communication	1
• usable for OP communication	
— reserved for OP communication	1
S7 message functions	
Number of login stations for message functions, max.	8

Symbol-related messages	Yes
Program alarms	Yes
simultaneously active Alarm-S blocks, max.	70; ALARM_S/SQ blocks or ALARM_D/DQ blocks
Alarm 8-blocks	Yes
• Number of instances for alarm 8 and S7 communication blocks, max.	300
• preset, max.	150
Process control messages	Yes
Number of archives that can log on simultaneously (SFB 37 AR_SEND)	4
Number of messages	
• overall, max.	512
• in 100 ms grid, max.	0
• in 500 ms grid, max.	256
• in 1000 ms grid, max.	256
Number of additional values	
• per message	1
• with 100 ms grid, max.	0
• with 500, 1000 ms grid, max.	1
Test commissioning functions	
Status block	Yes
Single step	Yes
Number of breakpoints	4
Status/control	
• Status/control variable	Yes
• Variables	Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters
• Number of variables, max.	70
Forcing	
• Forcing	Yes
• Forcing, variables	Inputs/outputs, bit memories, distributed I/Os
• Number of variables, max.	64
Diagnostic buffer	
• present	Yes
• Number of entries, max.	200
— adjustable	Yes
— preset	120
Configuration	
Configuration software	
• STEP 7	Yes
Programming	
• Command set	see instruction list

• Nesting levels	8
• Access to consistent data in process image	Yes
• System functions (SFC)	see instruction list
• System function blocks (SFB)	see instruction list
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
— HiGraph®	Yes
Number of simultaneously active SFCs	
— DPSYC_FR	2
— D_ACT_DP	4
— RD_REC	8
— WR_REC	8
— WR_PARM	8
— PARM_MOD	1
— WR_DPARM	2
— DPNRM_DG	8
— RDSYSST	1 to 8
— DP_TOPOL	1
Number of simultaneously active SFBs	
— RDREC	8
— WRREC	8
Know-how protection	
• User program protection/password protection	Yes
Dimensions	
Width	25 mm
Height	290 mm
Depth	219 mm
Weights	
Weight, approx.	720 g
last modified:	04/06/2018