



Main

Range of product	Modicon Premium Automation platform
Product or component type	CANopen bus master PCMCIA card
Software designation	CANopen standard
Software version	V4.02
Additional information	Unauthorized on TSX P57 153M/154M processor
Electrical connection	1 male connector SUB-D 9 + TAP junction CANopen bus connection

Complementary

Product compatibility	Modicon Premium TSXP57 Atrium TSXPCI or TPCX Device conforms to CANopen standard profile
Memory type	PCMCIA card III
Bus conformity class	M00
Communication port protocol	CANopen
Method of access	Master
Transmission rate	800 kbit/s 20 kbit/s 10 kbit/s 50 kbit/s 500 kbit/s 1000 kbit/s 250 kbit/s 125 kbit/s
Transmission support medium	2 twisted shielded pairs cable
Communication service	Management of bus operating modes Message handling (SDO) PDO cyclic exchanges
Number of modules per PLC per PC	1 Premium TSXP57
Current consumption	60 mA at 5 V DC
Marking	CE
Net weight	0.23 kg

Environment

Ambient air temperature for operation	0...60 °C
IP degree of protection	IP20
Standards	DR 303-2 DS 301 V4.02
Product certifications	CSA UL

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------