

NO LONGER AVAILABLE SIMATIC PANEL PC 477B 12"
TOUCH DISPLAY, 800X600 STANDARD FRONT W. USB
INTERFACE INTEL CELERON M 1,0 GHZ PROFIBUS DP 12 1 GB
RAM (DDR2) 2 X ETHERNET 1 GBIT/S 4 X USB 2.0, 500MA 1 X
RS232 (COM1) POWER SUPPLY DC 24V 2 CF-SLOTS W/O MASS
STORAGE

Display	
Screen diagonal	12 in
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Input device	
• Mouse, at front	No
Keyboard fonts	
• alphanumeric keyboard	No
Touch operation	
• Design as touch screen	Yes
Installation type/mounting	
central design	Yes
distributed design	No
Power loss	
In full configuration	24 V DC: max. 80 W (3 W included per slot)
Accessories	
Accessory components	Touch protective foil
Dimensions	
Operator control unit (W x H) in mm	400x310 (7 HU)
• Operator panel width	400 mm
• Operator panel height	310 mm
Install. dimensions, centralized design (W x H x D without optical drive) in mm	368x290x75
• Width	368 mm
• Height	290 mm
• Depth	75 mm
Weights	
Panel PC in central design, approx.	7.3 kg

last modified:

08/12/2017