

MLFB-Ordering data

6SL3224-0BE15-5UA0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		General tech. specifications	
Input		Power factor λ	0.85
Number of phases	3 AC	Offset factor $\cos \varphi$	0.95
Line voltage	380 ... 480 V ± 10 %	Efficiency η	0.97
Line frequency	47 ... 63 Hz	Sound pressure level (1m)	45 dB
Rated current with line reactor	1.80 A	Power loss	0.10 kW
Rated current without line reactor	2.10 A	Ambient conditions	
Output		Cooling	Internal air cooling
Number of phases	3 AC	Cooling air requirement	0.005 m ³ /s
Rated voltage	400 V	Installation altitude	1000 m
Rated power (LO)	0.55 kW / 0.75 hp	Ambient temperature	
Rated power (HO)	0.55 kW / 0.75 hp	Operation LO	0 ... 40 °C (32 ... 104 °F)
Rated current (LO)	1.70 A	Operation HO	0 ... 50 °C (32 ... 122 °F)
Rated current (HO)	1.70 A	Transport	-40 ... 70 °C (-40 ... 158 °F)
Max. output current	3.40 A	Storage	-25 ... 55 °C (-13 ... 131 °F)
Pulse frequency	4 kHz	Relative humidity	
Output frequency for vector control	0 ... 200 Hz	Max. operation	95 % RH, condensation not permitted
Output frequency for V/f control	0 ... 550 Hz		

Overload capability

Low Overload (LO)

1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.5 x rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s

High Overload (HO)

1.5 x output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 x output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

SIEMENS

Data sheet for SINAMICS Power Module PM240

MLFB-Ordering data

6SL3224-0BE15-5UA0



Figure similar

Mechanical data		Connections	
Degree of protection	IP20	Line side	
Size	FSA	Version	screw-type terminal
Net weight	1.10 kg	Conductor cross-section	1.00 ... 2.50 mm²
Width	73.0 mm	Motor end	
Height	173.0 mm	Version	Screw-type terminals
Depth	145.0 mm	Conductor cross-section	1.00 ... 2.50 mm²
		DC link (for braking resistor)	
		Version	Screw-type terminals
		Conductor cross-section	1.00 ... 2.50 mm²
		PE connection	On housing with M4 screw
		Max. motor cable length	
		Shielded	50 m
		Unshielded	100 m
Standards			
Compliance with standards		UL, cUL, CE, C-Tick (RCM), SEMI F47	
CE marking		Low-voltage directive 2006/95/EC	